



TIKKURILA

SUPI SAUNAPESU

SAUNA CLEANING DETERGENT

DESCRIPTION	Bleaching and lime-dissolving acidic cleaning agent.
RECOMMENDED USES	For saunas and other wet rooms.
PRODUCT FEATURES	Even though the product is acidic, it is gentle and non-corrosive. However, care should be taken when cleaning tile joints with concentrated and strong solutions. Do not use together with products containing chlorine.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



SUPI SAUNAPESU

TECHNICAL DATA

Paint product group 2012	013 Puupintojen pesuaineet sisäkäyttöön
Can sizes	0.5 l, 1 l
Application method	Brush or sponge.
Density (kg/l)	1.03 kg/l, ISO 2811
Storage	Protect from frost

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



SUPI SAUNAPESU

APPLICATION INSTRUCTIONS

Application conditions

The temperature of the air should be at least +5 °C, and the relative humidity of the air below 80 %.

Mixing components

Depending on the condition of the sauna, add 0.1 to 0.2 liters of Saunapesu to 5 liters of water. pH value of ready-to-use solution: approx. 2.

Depending on the condition of the sauna, add 0.1 to 0.2 liters of Saunapesu to 5 liters of water.

DISSOLVING LIME:

Use a 10–15% solution. Undiluted Supi Saunapesu can be used on persistent lime scale deposits and dirt stains.

BLEACHING SAUNA BENCHES:

Mix with an equal amount of water (1:1) and let work for approx. 15 minutes.

Note! Always rinse the benches with clean water after treatment.

Cleaning of tools

Clean tools with water.

Note

Note! Always rinse the benches with clean water after treatment.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.